

INVENGO ON METAL TAG OFFERING

Monza 4QT



About Invengo's RAIN RFID On Metal Tag offering

Invengo's diversified and specialized RAIN RFID (UHF) tag product portfolio offers global customers a broad range of options to address the increasing rugged RFID tag demand from various industries. Innovative broadband RFID antenna design enables end-users to reach and sustain consistently high levels of performance in all UHF frequency regions. Invengo's RAIN RFID rugged tags are available in multiple sizes and formats.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID (UHF) and NFC (HF) inlays, tags and connectivity solutions utilized in the Internet of Things (IoT). With a focus on RFID innovation, Invengo has created a leading product line in retail, library, (industrial) laundry, pharmaceutical, healthcare, (public) transportation and many other industries.

Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 600 people globally, Invengo is one of the largest publicly traded, RFID oriented companies in the world.

Key Benefits

- High performance for a wide range of industrial and metal asset management applications
- Compact slim design
- IP65 rated
- Serialized TID
- Excellent read range

Application Areas

- Asset Tracking
- Specialty metal device tracking
- IT asset tracking

On Metal Tag

XCTF-7020-FCC

Operating Frequency	902 to 928 MHz
Dimensions	70 x 20 x 3,4 mm (2.76 x .79 x 0.13 in)

XCTF-7020-EU

Operating Frequency	865 to 868 MHz
Dimensions	70 x 20 x 3,4 mm (2.76 x .79 x 0.13 in)

XCTF-9525-FCC

Operating Frequency	902 to 928 MHz
Dimensions	95 x 25 x 3,4 mm (3.74 x 0.98 x 0.13 in)

XCTF-9525-EU

Operating Frequency	865 to 868 MHz
Dimensions	95 x 25 x 3,4 mm (3.74 x 0.98 x 0.13 in)

General Product Specifications


RFID

Protocols Supported	EPCglobal C1 Gen 2, ISO/IEC18000-63
Integrated Circuit (IC)	Monza 4QT
EPC size	128 bits
User Memory	512 bits
TID	96 bits
Access password	32 bits
Kill password	32 bits

Environmental

Recommended* Operating Temperature	-40 °C to 85 °C (-40 °F to 185 °F) <i>* based on chip specifications</i>
IP Rating	65
Attach method	Rivets and/or 3M 300LSE tape

XCTF-7020-FCC/
XCTF-7020-EU



XCTF-9525-FCC/
XCTF-9525-EU



APAC

Invengo Technology Pte. Ltd
10 Kallang Avenue
#05-15 Tower 2, Aperia
Singapore 339510

Office: +65 6702 3909
sales.apac@invengo.com

Americas

Invengo Technology Corp.
2700-160 Sumner Blvd.
Raleigh, NC 27616
United States of America

Office: +1 919 890 0202
sales.americas@invengo.com

EMEA

Invengo Technologies
180 Voie Ariane – Athélia 1
13600 La Ciotat
France

T. +33 413 96 1111
sales.emea@invengo.com